

Technical data sheet SST 740 - 0,13 mm thick

SST 740 is our softest seam sealing tape and is mainly used on PU and PTFE coated material. Furthermore, it is used in the following areas: firefighting gears, rainwear, industrial filter, tents, waterproof boots and skiwear.

	<i>Method</i>	<i>Membrane</i>	<i>Adhesive</i>
Composition	N/A	Polyurethane	Polyurethane
Melting Range	Kofler Bench	180 – 185°C	132°C
Processing Temperature	N/A	N/A	-35°C – 100°C
UV-Stability	SAE J 1960	No	No
Hardness	D-2240	97 A	80 A
Tensile Strength	D-412	72,39 N/mm ²	37,23 N/mm ²
Appearance	Visual	Transparent to slightly amber	Tranparent
Standard Thickness	N/A	0.05 mm	0.08 mm
Ultimate Elongation	D-412	450 %	700 %
Freeze Point	D-1043	-28°C	N/A
Home Washing	N/A	Yes	Yes
Dry Cleaning	N/A	Yes	Yes

Good bonding with:

Non-woven
Polyester
PVC
Polyurethane

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for a particular application or the results to be obtained herein. The information is based on laboratory work with small-scale equipment and does not necessarily indicate any end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the product for the applications disclosed. Full –scale testing and end product performance are the responsibility of the end user. Gluetex GmbH shall not be liable for, and the customer assumes all risk and liability for any use or handling beyond Gluetex's direct control.

The seller makes no warranties, express or implied, including, but not limited to the implied warranties and fitness for a particular purpose.