

Technical data sheet UKF 438

UKF 438 is a solvent-free polyurethane adhesive film based on thermoplastic ester, which is extruded on medium heavy release paper and produced in different widths and thicknesses.

	<i>Method</i>	<i>Result</i>
Composition	N/A	Polyurethane
Melting Range	Kofler Bench	75 – 85°C
UV-Stability	SAE J 1960	No
Working Range	N/A	125 – 150°C
Gravity	ASTM D-792	1.20g/cm ³
Resistance against PVC Softener	Internal Method	Yes
Appearance	Visual	Transparent
Standard Thickness	N/A	0.13 mm
Dry Cleaning	N/A	Yes
Home Washing	N/A	Yes

Good bonding with:

Textiles

- Polyester
- Cotton
- Nylon
- Rayon
- Lycra
- Glass fiber
- Acrylic

Naturals

- Wood
- Leather
- Paper

Plastics

- ABS
- Polycarbonate
- PVC
- Polyurethane

Metals

- Aluminum
- Copper
- Steel

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for a particular application or the results to be obtained herein. The information is based on laboratory work with small-scale equipment and does not necessarily indicate any end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the product for the applications disclosed. Full –scale testing and end product performance are the responsibility of the end user. Gluetex GmbH shall not be liable for, and the customer assumes all risk and liability for any use or handling beyond Gluetex's direct control.

The seller makes no warranties, express or implied, including, but not limited to the implied warranties and fitness for a particular purpose.